





铸铁

暗杆闸阀






125Lb.法兰 10K 法兰 PN16 法兰 PN25 法兰

型号	1			3			104					
材料	A126 Class B			FC200			EN1561 GJL200			EN1561 GJL250		
规格	C83600			CAC406(BC6)			EN1982 CC491K			EN1982 CC491K		
工作压力	ASME • 2"~12"/200PSI-水·油·气(100°F) 125PSI-饱和蒸气 • 14"~24"/150PSI-水·油·气(100°F) 125PSI-饱和蒸气			JIS • 1.37MPa(-10~120°C)			EN1171(BS5150) • 16bar(-10~120°C)			EN1171(BS5150) • 25bar(-10~120°C)		
外观												
尺寸	L	H	W	L	H	W	L	H	W	L	H	W
1 1/2 inch	40mm			165	262	158						
2	50	178	245	180	276	158	178	245	158	216	290	200
2 1/2	65	190	272	158	190	302	158	190	272	241	313	200
3	80	203	297	158	200	332	158	203	297	283	350	224
4	100	229	355	195	230	384	195	229	355	305	400	250
5	125	254	397	195	250	435	195	254	397	381	448	280
6	150	267	465	220	270	497	220	267	465	403	520	300
8	200	292	561	280	290	608	280	292	561	419	612	355
10	250	330	669	310	330	721	310	330	669	457	728	400
12	300	356	778	355	350	838	355	356	778	502	835	400
14	350	381	904	450	381	975	450	381	904			
16	400	406	1039	500	406	1132	500	406	1039			
18	450	432	1151	560	432	1227	560	432	1151			
20	500	457	1264	630	457	1341	630	457	1264			
24	600	508	1473	710	508	1566	710	508	1473			
备注				带开度指示器			可以制造无铅铜阀座 带开度指示器			可以制造无铅铜阀座 带开度指示器		

铸铁

明杆闸阀




125Lb.法兰 10K 法兰 PN16 法兰 PN25 法兰 5K 法兰 10K 法兰

型号	6			8			183			7			38					
材料	A126B			FC200			EN1561 GJL200			FC200			FC200					
规格	C83600 or F6			CAC406(BC6)orSUS403			EN1982 CC491K or 410S21			CAC406(BC6)			CAC406(BC6)orSUS403orSUS304					
工作压力	ASME • 2"~12"/200PSI-水·油·气(100°F) 125PSI-饱和蒸气 • 14"~24"/150PSI-水·油·气(100°F) 125PSI-饱和蒸气			JIS • 1.37MPa(-10~120°C)			EN1171(BS5150) • 16bar(-10~120°C)			EN1171(BS5150) • 25bar(-10~120°C)			JIS B2031 • 0.69MPa(120°C) • 0.20MPa-饱和蒸气			JIS B2031 • 1.37MPa(120°C) • 0.69MPa-饱和蒸气		
外观																		
尺寸	L	H(开)	W	L	H(开)	W	L	H(开)	W	L	H(开)	W	L	H(开)	W			
1 1/2 inch	40mm			165	288	160							150	318	160			
2	50	178	308	180	308	160	178	308	160	216	361	200	160	336	160			
2 1/2	65	190	358	180	190	358	180	190	358	241	400	200	170	391	180			
3	80	203	404	180	200	404	180	203	404	283	447	224	180	446	180			
4	100	229	498	224	230	498	224	229	498	305	529	280	200	553	224			
5	125	254	588	224	250	588	224	254	588	381	633	280	220	645	224			
6	150	267	708	250	270	708	250	267	708	403	746	300	240	753	250			
8	200	292	918	280	290	918	280	292	918	419	936	355	260	938	280			
10	250	330	1120	300	330	1120	300	330	1120	457	1141	400	300	1158	355			
12	300	356	1312	355	350	1312	355	356	1312	502	1334	500	330	1381	400			
14	350	381	1539	450	381	1539	450	381	1539									
16	400	406	1793	500	406	1793	500	406	1793									
18	450	432	1995	560	432	1995	560	432	1995									
20	500	457	2194	600	457	2194	600	457	2194									
24	600	508	2670	710	508	2670	710	508	2670									
备注							可以制造无铅铜阀座			可以制造无铅铜阀座								




铸铁

截止阀

5K法兰 10K 法兰 PN16 法兰 10K 法兰

型号	4			79			37					
材料	FC200			EN1561 GJL200			FC200					
规格	CAC406(BC6)			EN1982 CC491K			CAC406(BC6)					
工作压力	昭和型 • 0.49MPa(80°C) • 0.69MPa(80°C) • 1.37MPa(-10~80°C)			昭和型 • 16bar(-10~120°C)			JIS B2031 • 1.37MPa(120°C) • 0.20MPa-饱和蒸气					
外观												
尺寸	L	H	W	L	H	W	L	H	W			
1 1/4 inch	32mm			140	197	140						
1 1/2	40	126	174	140	206	140						
2	50	142	207	150	235	140	150	235	140			
2 1/2	65	146	234	148	160	266	160	266	160			
3	80	153	265	158	175	293	160	293	160			
4	100	190	319	165	200	360	224	360	224			
5	125	205	373	195	225	406	224	406	224			
6	150	218	429	220	250	453	224	453	224			
8	200	230	532	245								
10	250											
12	300											
备注	用在低压筒略型			用在泵			可以制造无铅铜阀座			带开度指示器		

125Lb.法兰 10K 法兰 PN16 法兰

型号	32			34					
材料	A126B			FC200			EN1561 GJL200		
规格	C83600 or F6			CAC406(BC6)orSUS403			EN1982 CC491K or 410S21		
工作压力	ASME • 2"~12"/200PSI-水·油·气(100°F) 125PSI-饱和蒸气 • 14"~20"/150PSI-水·油·气(100°F) 100PSI-饱和蒸气			JIS B2031 • 1.37MPa(-10~120°C)			EN13789(BS5152) • 16bar(-10~120°C)		
外观									
尺寸	L	H(开)	W	L	H(开)	W	L	H(开)	W
1 1/2 inch	40mm			190	253	160			
2	50	203	265	180	265	180	203	265	180
2 1/2	65	216	289	200	289	200	216	289	200
3	80	241	329	224	329	224	241	329	224
4	100	292	367	280	367	280	292	367	280
5	125	330	398	315	398	315	330	398	315
6	150	356	457	355	457	355	356	457	355
8	200	495	561	450	561	450	495	561	450
10	250	622	665	500	665	500	622	665	500
12	300	698	803	560	700	560	698	803	560
14	350	787	890	600	787	600	787	890	600
16	400	914	1010	710	914	710	914	1010	710
18	450	965	1120	800	965	800	965	1120	800
20	500	978	1230	1000	978	1230	978	1230	1000
备注							可以制造无铅铜阀座		

CAST IRON VALVE

CAST IRON VALVE


铸铁

U型过滤器

		10K 法兰			PN16 法兰			10K 法兰			PN16 法兰													
型号	191A(快开型)												191B(螺栓连接阀盖)											
材料	FC200			EN1561 GJL200			FC200			EN1561 GJL200			FC200			EN1561 GJL200								
规格	SUS304			EN10088-1,1.4301			SUS304			EN10088-1,1.4301			SUS304			EN10088-1,1.4301								
工作压力	● 1.37MPa(-10~120°C)			● 16bar(-10~120°C)			● 1.37MPa(-10~120°C)			● 16bar(-10~120°C)			● 1.37MPa(-10~120°C)			● 16bar(-10~120°C)								
外观																								
尺寸	L	H1	H2	L	H1	H2	L	H1	H2	L	H1	H2	L	H1	H2	L	H1	H2						
2 inch	50mm	267	158	194	267	158	194	267	86	194	267	86	194	267	86	194	267	86	194					
2 1/2	65	295	167	223	295	167	223	295	95	223	295	95	223	295	95	223	295	95	223					
3	80	334	185	279	334	185	279	334	112	279	334	112	279	334	112	279	334	112	279					
4	100	427	237	273	427	237	273	427	129	273	427	129	273	427	129	273	427	129	273					
5	125	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-					
6	150	497	260	469	497	260	469	497	150	469	497	150	469	497	150	469	497	150	469					
8	200	685	330	685	685	330	685	685	190	685	685	190	685	685	190	685	685	190	685					
10	250	838	400	790	838	400	790	838	318	790	838	318	790	838	318	790	838	318	790					
12	300	857	430	1114	857	430	1114	857	350	1114	857	350	1114	857	350	1114	857	350	1114					

● 过滤网孔径尺寸

阀门尺码	h	P	目数换算
2"~4"	1.5mm	2.5mm	15
6"~12"	2.5mm	3.5mm	10




铸铁

Y型过滤器

		125Lb. 法兰		10K 法兰		PN16 法兰	
型号	33						
材料	A126B		FC200		EN1561 GJL200		
规格	A182 F304		SUS304		EN10088-1,1.4301		
工作压力	● 2"~12"/200PSI-水油(100°F) 125PSI-饱和蒸汽		● 1.37MPa(-10~120°C)		● 16bar(-10~120°C)		
外观							
尺寸	L	H	L	H	L	H	
1 1/2 inch	40mm						
2	50	220	135	220	135	220	
2 1/2	65	270	179	270	179	270	
3	80	290	190	290	190	290	
4	100	350	238	350	238	350	
5	125	390	270	390	270	390	
6	150	440	321	440	321	440	
8	200	540	384	540	384	540	
10	250	680	495	680	495	680	
12	300	840	574	840	574	840	
14	350	910	661	910	661	910	
16	400	1000	760	1000	760	1000	
18	450	1100	850	1100	850	1100	

● 过滤网孔径尺寸

阀门尺码	h	P	目数换算
2"~4"	1.5mm	2.5mm	15
5"~12"	2.0mm	3.0mm	12
14"~16"	2.5mm	3.5mm	10
18"	5.0mm	8.0mm	5



铸铁

球阀

		10K 法兰		
型号	78			
材料	FC200			
规格	SCS13A			
设计	两片式			
口径	全通径			
工作压力	1.37MPa 水·油·气 (120°C)			
外观				
尺寸	L	H	W	
1/2 inch	15mm	110	90	175
3/4	20	120	95	175
1	25	130	100	175
1 1/4	32	140	105	175
1 1/2	40	165	130	235
2	50	180	140	235
2 1/2	65	190	155	330
3	80	200	170	330
4	100	230	180	330
5	125	300	230	700
6	150	340	260	700
8	200	450	290	1000
10	250	530	-	-
12	300	620	-	-

备注 ● 250mm以上采用齿轮驱动

铸铁

止回阀

		125Lb. 法兰		10K 法兰		PN16 法兰		PN25 法兰	
型号	9				10				
材料	A126B		FC200		EN1561 GJL200				
规格	C83600 or F6		CAC406(BC6) or SUS403		EN1982 CC491K or 410S21				
工作压力	● 2"~12"/200PSI-水油(100°F) 125PSI-饱和蒸汽		● 1.37MPa(-10~120°C)		● 16bar(-10~120°C)		● 25bar(-10~120°C)		
外观									
尺寸	L	H	L	H	L	H	L	H	
1 1/2 inch	40mm		190	105					
2	50	203	110	200	110	203	110	200	
2 1/2	65	216	120	220	120	216	120	224	
3	80	241	135	240	135	241	135	248	
4	100	292	155	290	155	292	155	298	
5	125	330	180	360	180	330	180	372	
6	150	356	200	410	200	356	200	426	
8	200	495	230	500	230	495	230	516	
10	250	622	305	620	305	622	305		
12	300	698	355	700	355	698	355		
14	350	570	410	570	410	570	410		
16	400	630	470	630	470	630	470		
18	450	700	520	700	520	700	520		
20	500	770	570	770	570	770	570		
24	600	920	650	920	650	920	650		

型 旋启式 旋启式 旋启式 旋启式
备注 可以制造无铅铜阀座 可以制造无铅铜阀座

铸铁

止回阀

		10K 法兰			对夹								
型号	39					12		119		40		68WL	
材料	A126B		FC200		EN1561 GJL200								
规格	A182 F304		SUS304		EN10088-1,1.4301								
工作压力	● 1.37MPa(-10~120°C)		● 1.37MPa(-10~80°C)		● 1.37MPa(-10~80°C)		● ASME125 200PSI 水·油·气(80°C以下) ● BS-PN16 16bar(80°C以下) ● JIS10K 1.37MPa(80°C以下)						
外观													
尺寸	L	H	L	H	L	H	L	H	L	L			
1 1/2 inch	40mm		145	120	160	100			90				
2	50	200	115	160	130	180	110		90	54			
2 1/2	65	220	132	175	140	200	120		100	54			
3	80	240	145	185	150	210	135		115	57			
4	100	290	170	230	165	215	145		135	64			
5	125	360	200	255	180	255	165		150	70			
6	150	410	225	290	200	280	180		175	76			
8	200	500	260						220	95			
10	250								280	108			
12	300									143			
14	350									184			
16	400									191			
18	450									203			
20	500									219			
24	600									222			

型 旋启式 旋启式 升降式 升降式 对板对夹式
备注 带旁通阀 带旁通阀 快关型 快关型 快关型