

球墨铸铁

闸阀

		150Lb.法兰			10K 法兰			16K 法兰			PN25 法兰			PT.丝扣			10K 法兰																				
型号		192						69						183D						270						271											
材料	阀体	A536 65-45-12						FCD450-10						EN1563 GJL450-10						FCD-S																	
	阀座	C83600 or F6						CAC406(BC6) or SUS403						EN1982 CC491Kor410S21						13Cr.																	
规格		ASME						JIS						JIS(JV)						EN1171(BS5150)						JIS(JV)											
工作压力		●250PSI-水·油·气(-29~38℃) ●150PSI-饱和蒸气						●1.37MPa-水(120℃) ●1.18MPa-水·油·气(220℃)						●2.16MPa-水(120℃) ●1.96MPa-水·油·气(220℃)						●25bar(-10~120℃)						●1.37MPa-水(120℃) ●0.98MPa-水·油·气(220℃)											
外观																																					
尺寸		L	H(开)	W	L	H(开)	W	L	H(开)	W	L	H(开)	W	L	H(开)	W	L	H(开)	W	L	H(开)	W	L	H(开)	W	L	H(开)	W	L	H(开)	W	L	H(开)	W			
1/2 inch	15mm																																				
3/4	20																																				
1	25																																				
1 1/4	32																																				
1 1/2	40																																				
2	50	178	308	160	178	368	200	178	355	180	216	361	200	105	320	135	140	320	135																		
2 1/2	65	190	358	180	190	406	200	190	407	180	241	400	200																								
3	80	203	404	180	203	455	224	203	473	224	283	447	224																								
4	100	229	498	224	229	533	280	229	556	250	305	529	280																								
5	125	254	588	224	254	634	280	254	665	280	381	633	280																								
6	150	267	708	250	267	747	300	267	772	300	403	746	300																								
8	200	292	918	280	292	938	355	292	965	315	419	936	355																								
10	250	330	1120	300	330	1142	400	330	1172	400	457	1141	400																								
12	300	356	1312	355	356	1334	500	356	1371	450	502	1334	500																								
14	350				381	1539	450																														
16	400				406	1793	500																														
18	450				432	1995	560																														
20	500				457	2194	600																														
24	600				508	2670	710																														
备注		阀座与阀杆材质青铜的产品，不能用于120℃以下的水之外流体																																			

球墨铸铁

截止阀

		150Lb.法兰			10K 法兰			16K 法兰			PN25 法兰			PT.丝扣			10K 法兰																				
型号		193						71						272						273																	
材料	阀体	A536 65-45-12						FCD450-10						EN1563 GJL450-10						FCD-S																	
	阀座	C83600 or F6						CAC406(BC6) or SUS403						EN1982 CC491Kor410S21						13Cr.																	
规格		ASME						JIS						JIS(JV)						EN13789(BS5152)						JIS(JV)											
工作压力		●250PSI-水·油·气(-29~38℃) ●150PSI-饱和蒸气						●1.37MPa-水(120℃) ●1.18MPa-水·油·气(220℃)						●2.16MPa-水(120℃) ●1.96MPa-水·油·气(220℃)						●25bar(-10~120℃)						●1.37MPa-水(120℃) ●0.98MPa-水·油·气(220℃)											
外观																																					
尺寸		L	H(开)	W	L	H(开)	W	L	H(开)	W	L	H(开)	W	L	H(开)	W	L	H(开)	W	L	H(开)	W	L	H(开)	W	L	H(开)	W	L	H(开)	W	L	H(开)	W			
1/2 inch	15mm																																				
3/4	20																																				
1	25																																				
1 1/4	32																																				
1 1/2	40																																				
2	50	203	265	180	203	265	180	203	265	180	230	265	180	140	206	135	180	206	135																		
2 1/2	65	216	289	200	216	289	200	216	289	200	290	289	200																								
3	80	241	329	224	241	329	224	241	329	224	310	329	224																								
4	100	292	367	280	292	367	280	292	367	280	350	367	280																								
5	125	356	398	315	356	398	315	356	398	315	400	398	315																								
6	150	406	457	355	406	457	355	406	457	355	480	457	355																								
8	200	495	561	450	495	561	450	495	561	450	600	561	450																								
10	250	622	665	500	622	665	500	622	665	500																											
12	300	698	800	560	698	800	560	698	800	560																											
备注		阀座与阀杆材质青铜的产品，不能用于120℃以下的水之外流体																																			

球墨铸铁

旋启式止回阀

升降式止回阀

		150Lb.法兰			10K 法兰			16K 法兰			PN25 法兰			PT.丝扣			10K 法兰																						
型号		194						70						274						275																			
材料	阀体	A536 65-45-12						FCD450-10						EN1563 GJL450-10						FCD-S																			
	阀座	C83600 or F6						CAC406(BC6) or SUS403						EN1982CC491Kor410S21						13Cr.																			
规格		ASME						JIS						JIS(JV)						EN1171(BS5150)						JIS(JV)													
工作压力		●250PSI-水·油·气(-29~38℃) ●150PSI-饱和蒸气						●1.37MPa-水(120℃) ●1.18MPa-水·油·气(220℃)						●2.16MPa-水(120℃) ●1.96MPa-水·油·气(220℃)						●25bar(10 120℃)						●1.37MPa-水(120℃) ●0.98MPa-水·油·气(220℃)													
外观																																							
尺寸		L	H	L	H	L	H	L	H	L	H	L	H	L	H	L	H	L	H	L	H	L	H	L	H	L	H	L	H	L	H	L	H	L	H				
1/2 inch	15mm																																						
3/4	20																																						
1	25																																						
1 1/4	32																																						
1 1/2	40																																						
2	50	203	110	230	110	230	115	200	110	140	68	150	68	180	76																								
2 1/2	65	216	120	216	120	216	130	220	120	220	120																												
3	80	241	135	241	135	241	155	240	155	240	155																												
4	100	292	155	292	155	292	180	290	178																														
5	125	330	180	330	180	330	215	360	205																														